

## Technical data sheet



## Quick plaster FOR QUICK INDOOR REPAIRS

**T**he quick plaster of the line **BRIKO K2** is ideal for quick repairs on indoor surfaces. Obtained by milling and then baking chalk stone, the product is known for its speed and ease of use.

### Features:

ideal for quick repairs on internal surfaces, the **quick plaster** of the line **BRIKO K2** has a rougher appearance compared to plaster for finishing, in order to facilitate its applicability. The visible surface however must be finished with scagliola or skimming plaster.

### Technical specifications:

<i>Appearance of the product:</i>	powder
<i>Colour:</i>	white
<i>Application temperature:</i>	+5°C to +35°C
<i>Setting start time:</i>	approximately 5 - 8 minutes

## Usage methods:

### Instructions for use:

arrange in a container 1 (one) part of clean water, and 2/3 of plaster. Pour the product and then mix manually and/or with a mechanical stirrer at a low number of revolutions (max 30 seconds), up to form a creamy and smooth mix. It is recommended to prepare a correct amount to be used within 5 minutes, in view of the rapidity of the product. Therefore, it is recommended to prepare everything you need, before you begin any work.

### Warning:

the **quick plaster** of the line **BRIKO K2** is to be used at temperatures between 5 °C and 35 °C. If the temperature is too low, drying becomes too slow and the product may be damaged by frost. At high temperatures, drying becomes too fast, which may cause micro-fissures. After the application, ventilate the premises to allow proper drying and to prevent the formation of mildew.

**Use the quick plaster of the line BRIKO K2 in its original state, without the addition of other components.**

### Uses:

thanks to its characteristics of strength and speed of set, the **quick plaster** of the line **BRIKO K2** is used for quick fastening of door frames, windows, and to lock the corrugated tubes within the tracks and for the filling of the traces or holes on the walls.



Sistem Certification Quality  
UNI EN ISO 9001:2008 Cert. SGS N° IT07/0886

### Supply:

boxes and paper bags:



Box: 1 Kg.

COD. EAN:  
8032628010170



Paper bag: 4 Kg.

COD. EAN:  
8032628010262

### Storage:

store the packages on wooden platforms, in a dry place, away from moisture and from any dripping. The material, if stored in a dry place on wooden pallets, can be stored for up to 10 months.

### Application legend:



**PROCESSING TIME:**  
about 5 minutes.



**FOR INDOOR USE.**

Excellent mechanical strength.

Easy to apply.



**APPLICATION TEMPERATURE:**  
5°C to 35°C.



**RECOMMENDED TOOLS:**  
spatula and trowel.

Quick setting.

### Notes:

*The above information refers to laboratory testing; in practical applications on site it may differ according to the conditions of implementation. The user should however verify the suitability of the product for the intended application, taking all responsibility for its use. The company Prima reserves the right to alter technical specifications without prior notice.*